



Hollex Fixed portlights and portlight trims

Brass

Fixed portlights, made of brass and with toughened glass. The portlights have a ground finish whereas the portlight trims are made of polished brass.

Glass diam.	Spigot (mm)	Diam. (mm)	Portlight Cat. no.	Portlight trim Cat. no.
5"	145	175	0915	0945
6"	170	200	0916	0946
7"	195	230	0917	0947
8"	225	260	0918	0948
10"	280	315	0920	0950



Hollex Opening and fixed portlights

Stainless steel

These opening and fixed portlights are made of stainless steel 304 and have toughened glass. Supplied complete with portlight trim. Suitable for a bulkhead thickness of 4 - 15 mm. The opening and fixed portlights are both available in three sizes. Mosquito screens are available for the opening portlights.

Glass diam. (mm)	Spigot (mm)	Overall diam. (mm)	Opening portlight Cat. no.	Mosquito screen Cat. no.	Trim Cat. no.
100	116	165	0934	0924	-
125	141	190	0935	0925	0955
150	166	215	0936	0926	0956
200	215	265	-	-	0957



Hollex Opening portlights

Stainless steel

These opening portlights are made of stainless steel 304 and have toughened glass. Supplied complete with portlight trim. Suitable for a bulkhead thickness of 4 - 16 mm. Mosquito screens are available for all sizes.

Glass diam.	Spigot (mm)	Overall diam. (mm)	Portlight Cat. no.	Mosquito screen Cat. no.
6"	160	218	0901	0911
8"	210	269	0902	0912
10"	261	320	0903	0913



Hollex deck- and escape hatches

Hollex Deck and escape hatches

The frames of these deck and escape hatches are made of 18-8 stainless steel and are hand- and electro polished to protect against corrosion. A neoprene seal and an adjustable lever ensure complete tightening. The hatches come with a smoke coloured, 12 mm thick unbreakable acrylic top. They are suitable for areas II, III and IV and comply with ISO 12216. Easy to operate stainless steel adjusters allow the hatches to be opened 180°. The deck hatches can only be opened from the inside by means of black nylon levers. The escape hatches can be opened both from inside and outside. Inside opening by means of black nylon levers, outside opening by means of stainless steel levers. An extra lever (not shown) makes sure you can lock the hatch from the inside when leaving your vessel.

Outer radius corners : 64 mm

Inner radius corners : 32 mm

Spigot dimensions (mm)	Overall dimensions (mm)	Deck hatch Cat. no.	Escape hatch Cat. no.
419 x 419	483 x 483	1130	1140
495 x 495	559 x 559	1131	1141
610 x 610	674 x 674	1132	1142
788 x 788	852 x 852	1133	1143